C200L Scanner-Dimensioner



PC Shipping and Freight Applications

The Cubetape C200L is designed for use in general shipping and freight applications and will:

- · eliminate errors and guesswork
- improve efficiency and reduce overheads
- improve operations
- integrate easily with existing systems

Specifications:



Specifications:		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Dimensioning	Tape Accuracy Output US/Metric Min/max	11/16 (27mm) x 10ft (3m) +/- 1/2" (10mm) 1", 1/2", m, cm 2"/4cm, 16ft/5m
Scanning	Image Type Symbologies	Best in class CMOS All Common 1D, 2D
Comms	Wireless 2.4G Bluetooth V5 USB C Port	Long Range HID, USB Serial (200 m outdoor line of sight) Direct (HID), Application (SPP), Low Energy (BLE) Data Transfer, Recharge, Firmware Update
Functions	Data Packets Modes Control Characters	Single Item, Multi Item, Online, Batch, Alibi Highly Configurable
Power	Li-Po Battery Duty Cycle Standby	Industrial 1200mAh, maximum 2 hour recharge, replaceable 8 hour minimum @ high duty cycle 30 day minimum
Usability	Single Button LEDs Buzzer	Power/Scan/Dimension Pairing and Power indications. Decode/Connect/Config indications
Physical	Size Weight	5.8 x 3.3 x 1.5in/148 x 84 x 38mm 13oz/360g
Regulatory	EMI/RFI ROHS	FCC Part 15 Class B, ICES, EU EMC Directive, Taiwan EMC Complies 2002/95/EEC
Other	Inclusions Warranty Working Temperature Humidity Ambient Light	USB C Cable, 2.4G RF Dongle Minimum 12 months on electronics*, excluding accessories - 20 to 160 F / -30 to +70C 5% to 95% relative humidity (no condensation) Works in normal indoor and outdoor settings
Options	Charge Cradles Tape Cassettes Protective Sleeve	1 Way, 5 Way, Holster 5m, 7.5m Silicon
Spares	Battery, Tape Cassette	

Note: *Warranty period can vary by region.