

UROVO

Enterprise Mobile Computer

DT40

- 4" Touch Screen & Keypad Dual Input
Chic and compact
- Fast & Seamless Wi-Fi Roaming
Switching between multiple APs fast and stable
- Bold Sound Feedback
Enhanced speaker, clear at noisy environment
- Excellent Performance
Powered by Octa-core Processor
- Precise 1D/2D Decoding
Market-leading barcode scan engine, distortion barcodes in microseconds



Octa-core High
Performance Processor



IP67
Sealing



1.5M
Drop Resistance




UEE UROVO
Enterprise Enabler

DT40 Enterprise Mobile Computer

Specifications

UROVO



CPU

Octa-core 1.8GHz



O.S.

Android 9.
(Upgradeable to Android 12)



Memory

3GB RAM / 32GB ROM
2GB RAM / 16GB ROM (optional)
Micro-SD card, Up to 128 GB



Display

4 inch display, 480×800



Touch panel

Ultra sensitive capacitive touch panel with Corning Gorilla Glass, support multi-touch, works with gloves and wet fingers



Dimensions

164.5*68.6*17.5mm
6.48in×2.7in× 0.69in
Weight: 279g
(include battery)



Scanning

Support all international standards 1D/2D barcode



Audio

Microphone
Speaker
Receiver



Main battery

Capacity: 3.85V 4500mAh



Camera

Front-2MP
Rear 13MP with flash



Notifications

High Power Speakers
Audio
Vibration
LED and so on



Buttons

21 key numeric with FN keys,
PWR key, Vol+/- key, PTT key,
scan key*2
supports on-screen keypad



Slots

2×Nano-SIM slots



Network Connections

4G/ 3G/ 2G
Bluetooth: 4.2+BR/EDR+BLE
Wi-Fi: IEEE802.11a/b/g/n/ac/ d/e/
h/i/k/r/v/w protocol
(2.4G/5G dual band Wi-Fi)



Positioning

GPS, BEIDOU
GLONASS
A-GPS, Galileo



Protection

IP67
1.5m drop resistance



Environment

Operating Temp.: -20 ~ +60°C(-4°F to 140°F)
Storage Temp.: -40 ~ +70°C(-40°F to 158°F)
Humidity: 5%RH ~ 95%RH ((No condensation)



Accessories

Standard Accessories: adaptor, cable,
battery, hand Strap
Optional Accessories: Single Charging Cradle,
4-Slot Charging Cradle, 4-Slot Battery Charging
Cradle, gun grip, Screen Protector, holster,
Boot Case

Urovo Technology Co., Ltd.

• Tel: 86 755-22673926 • Website: en.urovo.com • E-mail: urovo@urovo.com
• Address: Room 613,6/F.,Asia Trade Centre,79 Lei Muk Road,Kwai Chung,N.T.,Hong Kong

* This page is subject to change
without prior notice

UROVO

UROVO DT40

Specifications



UROVO Technology Co., Ltd.



Specifications

Performance	Model	UROVO DT40
	O.S.	Android 9.0 (Upgradeable to Android 12)
	Processor	Octa-core 1.8GHz
	Memory	RAM: 3 GB, ROM: 3 2 GB RAM: 2 GB, ROM: 1 6 GB (optional)
	Extended memory	Micro SD card, Up to 256 GB
Basic specifications	Dimensions	164.5*68.6*17.5mm
	Weight	279g
	Display	4 inch display, 480×800
	Touch Screen	Ultra sensitive capacitive touch panel with Corning gorilla cover glass, support multi-touch, works with gloves and wet fingers
	Main battery	Capacity: 3.85V 4500mAh
	Charging time	Less than 4 hours
	Buttons	Navigator key: Back, Home, Menu Numeric key: 0-9, Android standard key define Control key: Delete, Backspace, TAB key, "." 1Aa key: Switch numeric and Alphabet Fn key: F1-F4, Android standard define PWR key, Vol+/- key, PTT key, scan key
	Camera	Front 2MP, Rear 13MP with flash
	Sensors	Light + Accelerator+ Proximity
	Scanning	1D/2D barcode reader Can read all international standards 1D/2D barcode; Can read barcode displayed on screens and colored barcode;
	Slots	Micro SD/TFx1 , Nano-SIMx2
	Audio	Microphone, Speaker, Receiver
	Interfaces	USB Type-C、3.5mm ear phone jack、Pogo pin
Network Connections	Positioning	GPS, A-GPS, BEIDOU, GLONASS, Galileo
	WAN	Dual-SIM, Dual-Standby
		4G, 3G, 2G
	Bluetooth	BT 4.2 + BR/EDR + BLE
Wi-Fi	2.4G/5G, IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w Roaming: 802.11r /OKC/ PMKID caching	
Environment	Temperature	-20°C to 60°C (-4°F to 140°F)
	Storage	-40°C to 70°C (-40°F to 158°F)
	Humidity	5%RH ~ 95%RH (No condensation)
	Drop Specification	Multiple 5 ft./1.5 m drop to concrete at room temperature
	Sealing	IP67



Data Capture Specifications

1) Camera

Rear Camera	
functions	Flash light, Auto-focus, Video
Pixels	13MP
Front Camera	
Pixels	2MP, Fix-focus,

2) Scanner Engine

Option 1	2D Imager Engine Specifications
Scan Angels Tilt	360°
Scan Angels Pitch	±60°
Scan Angels Skew	±60°
Laser safety level	Class 2
Barcodes support	Linear: UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, MSI, Telepen, Trioptic, China Post 2D Stacked: PDF417, MicroPDF417, GS1 Composite 2D Matrix: Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code
Option 2	2D Imager Engine Specifications
Scan Angels Tilt	360°
Scan Angels Pitch	±60°
Scan Angels Skew	±60°
Laser safety level	Class II
Barcodes support	Linear: Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32(PARAF), EAN-UCC Emulation, GS1 Data Bar 2D Stacked: Codablock A, Codablock F, PDF417, MicroPDF417 2D Matrix: Aztec Code, Data Matrix, MaxiCode, QR Code, Chinese Sensible (Han Xin), Grid Matrix, Dot Code Postal: Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet

3) RFID(HF)



RFID	HF
Protocol	ISO15693 ISO14443: ISO14443 Type A, ISO14443 Type B MIFARE: Mifare S50, Mifare S70, Mifare UltraLight, Mifare Pro, Mifare Desfire、FeliCa
Frequency	13.56MHz
Reading Distance	Read distance 0-6cm (ISO15693),0-4cm(ISO14443A/B)

Network Connections

1) Positioning

Positioning	Specification
Mode	GPS、A-GPS、BeiDou、GLONASS、Galileo
Frequency	GPS (L1 1.575GHz C/A code) , BeiDou (B1 1.561GHz) , GLONASS(L1 1.602GHz), Galileo (E1 1.589 GHz / E2 1.561 GHz)
Cold start time	Less than 40s
Max channel	31 channel
sensitivity	-130dB(SNR value 40dBHz)
Precision	5-10 Meters (open space)

2) Wireless LAN

WLAN	Specification
Protocol	IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w protocol (2.4G/5G dual band Wi-Fi)
Frequency	2.4G、5G
Security and Encryption	EAP-TLS, EAP-TTLS, PEAP-MSCHAPv2, PEAP-TLS, PEAP-GTC, PWD, SIM, AKA WEP, WPA/WPA2-PSK, WAPI, WAPI-PSK
Fast roaming	Support 802.11r fast roaming

3) Wireless WAN

WAN	Specification
Mode	Dual SIM Dual Standby
Worldwide Radio Frequency Band	TD-LTE(B34/B38/B39/B40/B41) FDD-LTE(B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B19/B20/B25/B26/B28A/B28B/B66)
	WCDMA(B1/B2/B4/B5/B8) TD-SCDMA(B34/B39) CDMA2000 1x EV-DO Rev.A BC0 (800 MHz)
	CDMA 1x GSM/EDGE/GPRS(850/900/1800/1900)



4) Wireless PAN

BT	Specification
Mode	BT 4.2+BR/EDR+BLE
Range	More than 10 meters

Optional Accessories

	Type
Accessory	Single charging cradle(1 terminal, 1 battery charging), 4-slot charging cradle, 4-slot battery charging cradle, pistol grip, hand strap, Boot case