



# Pro-X Hybrid Kiosk Technical Specifications (TCx 800 Option)

Pro-X HYBRID KIOSK FEATURES	
Product Name	Pro-X Hybrid Kiosk
Model	6900-1K0
Product Description	The Pro-X Hybrid Kiosk is a tabletop self-service solution comprised of the kiosk base unit and a TCx 800 All-in-One POS. You must order a Pro-X Hybrid Kiosk (Machine Type Model 6900) and a TCx 800 All-in-One POS (Machine Type Model 6200) together for a complete solution.
Core Cabinet	<ul style="list-style-type: none"> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Zebra Symbol DS7708 scanner - Black version</li> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Zebra Symbol DS7708 scanner - Brilliant White version</li> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Datalogic Magellan 3410VSI scanner - Black version</li> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Datalogic Magellan 3410VSI scanner - Brilliant White version</li> </ul>
Core Cabinet Key Lock	The core module cabinet is accessible through a front panel door that is locked in place with a key. Select from 5 core cabinet key locks.
Printer	Toshiba 80 mm width high-performance KIOSK Thermal Printer KOP-3S01

Pro-X HYBRID KIOSK OPTIONAL FEATURES	
Rotating Base	Optional rotating base is available in black to support hybrid cashier functionality.
Transaction Awareness Light	Pro-X Hybrid Kiosk provides an optional transaction-awareness light (TAL). These lights are used by the POS application to communicate when assistance is needed, transaction status and security information to the shopper assistant (SA).
Pinpad Mounts (Pinpad not included)	<ul style="list-style-type: none"> <li>- Verifone MX925 Pinpad Mounting Bracket</li> <li>- Verifone MX915 Pinpad Mounting Bracket</li> <li>- Ingenico 250 Pinpad Mounting Bracket</li> <li>- Ingenico 480 Pinpad Mounting Bracket</li> <li>- Ingenico Lane 3000 Pinpad Mounting Bracket</li> <li>- Ingenico Lane 7000 Pinpad Mounting Bracket</li> </ul>
Pinpad Arm	Short or long pinpad arm in black or white pending your pinpad of choice.
Voltage Options	<ul style="list-style-type: none"> <li>- Low Voltage option (110-120V AC, 60 Hz)</li> <li>- High voltage option (220-240V AC, 50 Hz)</li> </ul>
Custom Colors	Custom colors can be ordered for an additional setup charge and a minimum order quantity. Please review with your sales representative for additional details.

TCx 800 ALL-IN-ONE POS: FEATURES	
TCx 800 All-in-One POS (Machine Type Model 6200)	Select from three TCx 800 All-in-One POS Systems with: <ul style="list-style-type: none"> <li>- 15" (If planning to run CHEC SW when available)</li> <li>- 15.6"</li> <li>- 18.5"</li> </ul>
TCx 800 All-in-One POS 6200 Models	10C, 103, 105, 107, E0C, E03, E05, E07, 11C, 113, 115, 117, E1C, E13, E15, E17, 13C, 133, 135, 137, E3C, E33, E35, E37
TCx 800 All-in-One POS Processor	Intel 7th Generation uSeries processors: <ul style="list-style-type: none"> <li>- Celeron 3965U</li> <li>- Core i3-7100U</li> <li>- Core i5-7300U</li> <li>- Core i7-7600U</li> </ul>
TCx 800 All-in-One POS Memory	8GB, 16GB, or 32GB DDR4
TCx 800 All-in-One POS Storage	<ul style="list-style-type: none"> <li>- 128 GB, 256 GB or 512 GB PCIe NVMe M.2 SSD</li> <li>- Up to 2x SSDs supported</li> <li>- RAID support (i5/i7 models)</li> </ul>
TCx 800 All-in-One POS Powered Connector options (System)	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>USB Mix</p>  <ul style="list-style-type: none"> <li>- 2x USB 2.0</li> <li>- 3x Powered USB (12V)</li> <li>- 1x Powered USB (24V)</li> <li>- 1x Power-in (24V)</li> <li>- 1x Cash Drawer (SDL)</li> <li>- 1x Cash Drawer (RJ11)</li> </ul> </div> <div style="width: 45%;"> <p>RS232 Mix</p>  <ul style="list-style-type: none"> <li>- 2x Powered RS-232 (12V or 5V)</li> <li>- 2x USB 2.0</li> <li>- 1x Powered USB (12V)</li> <li>- 1x Powered USB (24V)</li> <li>- 1x Power-in (24V)</li> <li>- 1x Cash Drawer (SDL)</li> <li>- 1x Cash Drawer (RJ11)</li> </ul> </div> </div>

TCx 800 All-in-One POS Primary Display	15" (4:3) or 15.6" (16:9) or 18.5" (16:9) (Black version) 15" (4:3) or 15.6" (16:9) (Brilliant White version) - Back-lit LCD - Bezel-less 10 point PCAP Touch Sensor
TCx 800 All-in-One POS Top Mountable	2x20 Customer Display
TCx 800 All-in-One POS Rear Mountable	10.1" (16:9) Customer Display (touch or non-touch - requires FC1026 Bracket)
TCx 800 All-in-One POS Head Mount	Select from a Black or Brilliant White mount plate.

TCx 800 ALL-IN-ONE POS: OPERATING SYSTEM	SUPPORT
No Preload	Do not preload any OS in the system unit
Windows 10 IoT Enterprise 2016 LTSB	Pre-load Windows 10 (64-bit) OS
Windows 10 IoT Enterprise 2019 LTSC	Pre-load Windows 10 (64-bit) OS

ITEM	HEIGHT	WIDTH	DEPTH
<b>Pro-X Hybrid Kiosk with Short Pin Pad Arm</b>			
TCx 800 15"	622.23 mm (24.5 in)	410.76 mm (16.17 in)	329.88 mm (13 in)
TCx 800 15.6"	610.58 mm (24.04 in)	427.41 mm (16.83 in)	329.88 mm (13 in)
TCx 800 18.5"	623.88 mm (24.56 in)	461.21 mm (18.16 in)	329.88 mm (13 in)
<b>Pro-X Hybrid Kiosk with TAL and Short Pin Pad Arm</b>			
TCx 800 15"	686.93 mm (27.04 in)	410.76 mm (16.17 in)	329.88 mm (13 in)
TCx 800 15.6"	686.93 mm (27.04 in)	427.41 mm (16.83 in)	329.88 mm (13 in)
TCx 800 18.5"	686.92 mm (27.04 in)	461.21 mm (18.16 in)	329.88 mm (13 in)
<b>Pro-X Hybrid Kiosk with Long Pin Pad Arm</b>			
TCx 800 15"	622.23 mm (24.5 in)	583.05 mm (22.95 in)	329.88 mm (13 in)
TCx 800 15.6"	610.58 mm (24.04 in)	599.70 mm (23.23.61 in)	329.88 mm (13 in)
TCx 800 18.5"	623.88 mm (24.56 in)	633.50 mm (24.94 in)	329.88 mm (13 in)
<b>Pro-X Hybrid Kiosk with TAL Long Pin Pad Arm</b>			
TCx 800 15"	688.27 mm (27.10 in)	583.05 mm (22.95 in)	329.88 mm (13 in)
TCx 800 15.6"	686.93 mm (27.04 in)	599.70 mm (23.61 in)	329.88 mm (13 in)
TCx 800 18.5"	688.27 mm (27 1/8 in)	633.50 mm (24.94 in)	329.88 mm (13 in)
<b>Pro-X Hybrid Kiosk with Rotating Base and Short Pin Pad Arm</b>			
TCx 800 15"	622.23 mm (24.5 in)	410.76 mm (16.17 in)	329.88 mm (13 in)
TCx 800 15.6"	610.58 mm (24.04 in)	427.41 mm (16.83 in)	329.88 mm (13 in)
TCx 800 18.5"	623.88 mm (24.56 in)	461.21 mm (18.16 in)	329.88 mm (13 in)
<b>Pro-X Hybrid Kiosk with TAL, Rotating Base and Short Pin Pad Arm</b>			
TCx 800 15"	686.93 mm (27.04 in)	410.76 mm (16.17 in)	329.88 mm (13 in)
TCx 800 15.6"	686.93 mm (27.04 in)	427.41 mm (16.83 in)	329.88 mm (13 in)
TCx 800 18.5"	686.92 mm (27.04 in)	461.21 mm (18.16 in)	329.88 mm (13 in)
<b>Pro-X Hybrid Kiosk with Rotating Base and Long Pin Pad Arm</b>			
TCx 800 15"	622.23 mm (24.5 in)	583.05 mm (22.95 in)	329.88 mm (13 in)
TCx 800 15.6"	610.58 mm (24.04 in)	599.70 mm (23.61 in)	329.88 mm (13 in)
TCx 800 18.5"	623.88 mm (24.56 in)	633.50 mm (24.94 in)	329.88 mm (13 in)
<b>Pro-X Hybrid Kiosk with TAL, Rotating Base and Long Pin Pad Arm</b>			
TCx 800 15"	688.27 mm (27.10 in)	583.05 mm (22.95 in)	329.88 mm (13 in)
TCx 800 15.6"	686.93 mm (27.04 in)	599.70 mm (23.61 in)	329.88 mm (13 in)
TCx 800 18.5"	688.27 mm (27.10 in)	633.50 mm (24.95 in)	329.88 mm (13 in)

TCB15058-USEN-01  
Released March, 2021

# Pro-X Hybrid Kiosk Technical Specifications (T10 Option)

Pro-X HYBRID KIOSK FEATURES	
Product Name	Pro-X Hybrid Kiosk
Model	6900-1K0
Product Description	The Pro-X Hybrid Kiosk is a tabletop self-service solution comprised of the kiosk base unit and a T10 All-in-One POS. You must order a Pro-X Hybrid Kiosk (Machine Type Model 6900) and a T10 All-in-One POS (Machine Type Model 4818) together for a complete solution.
Core Cabinet	<ul style="list-style-type: none"> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Zebra Symbol DS7708 scanner - Black version</li> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Zebra Symbol DS7708 scanner - Brilliant White version</li> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Datalogic Magellan 3410VSI scanner - Black version</li> <li>- Pro-X Hybrid Kiosk Cabinet, kiosk printer and Datalogic Magellan 3410VSI scanner - Brilliant White version</li> </ul>
Core Cabinet Key Lock	The core module cabinet is accessible through a front panel door that is locked in place with a key. Select from 5 core cabinet key locks.
Printer	Toshiba 80 mm width high-performance KIOSK Thermal Printer KOP-3S01

Pro-X HYBRID KIOSK OPTIONAL FEATURES	
Rotating Base	Optional rotating base is available in black to support hybrid cashier functionality.
Transaction Awareness Light	Pro-X Hybrid Kiosk provides an optional transaction-awareness light (TAL). These lights are used by the POS application to communicate when assistance is needed, transaction status and security information to the shopper assistant (SA).
Pinpad Mounts (Pinpad not included)	<ul style="list-style-type: none"> <li>- Verifone MX925 Pinpad Mounting Bracket</li> <li>- Verifone MX915 Pinpad Mounting Bracket</li> <li>- Ingenico 250 Pinpad Mounting Bracket</li> <li>- Ingenico 480 Pinpad Mounting Bracket</li> <li>- Ingenico Lane 3000 Pinpad Mounting Bracket</li> <li>- Ingenico Lane 7000 Pinpad Mounting Bracket</li> </ul>
Pinpad Arm	Short or long pinpad arm in black or white pending your pinpad of choice.
Voltage Options	<ul style="list-style-type: none"> <li>- Low Voltage option (110-120V AC, 60 Hz)</li> <li>- High voltage option (220-240V AC, 50 Hz)</li> </ul>
Custom Colors	Custom colors can be ordered for an additional setup charge and a minimum order quantity. Please review with your sales representative for additional details.

T10 ALL-IN-ONE POS: FEATURES	
T10 All-in-One POS (Machine Type Model 4818)	15"
T10 All-in-One POS 4818 Models	T10, ET1
T10 All-in-One POS Processor	Intel® Celeron® J1900 - up to 2.42 GHz
T10 All-in-One POS Memory	4GB Memory (1 DIMM & Upgradeable), up to 8GB max
T10 All-in-One POS Storage	128GB SATA M.2 2280 SSD
T10 All-in-One POS Powered Connector Options (System)	<ul style="list-style-type: none"> <li>- (1) x 24V Powered USB</li> <li>- (2) x 12V Powered USB</li> <li>- (4) x 5V USB 3.0</li> <li>- (4) x RS232 (2-DB-9, 2 RJ50)</li> <li>- (1) x Mini Display Port/VGA</li> <li>- (1) x Drawer Port Minimum – RJ12</li> <li>- (1) x RJ45 Ethernet</li> <li>- (1) x 3.5mm 4 conductor combo audio jack (Line-out and Mic-in)</li> <li>- Stereo Speaker/PC Beeper</li> </ul>
T10 All-in-One POS Primary Display	<ul style="list-style-type: none"> <li>- 15" 4:3 1024x768 resolution</li> <li>- 250 nits</li> <li>- LED backlight with 50K hours of life</li> <li>- Bezel Free with 10-points PCT touch"</li> </ul>
T10 All-in-One POS Top Mountable	<ul style="list-style-type: none"> <li>- MSR</li> <li>- MSR &amp; iButton</li> </ul>

T10 ALL-IN-ONE POS: OPERATING SYSTEM	SUPPORT
No Preload	Do not preload any OS in the system unit
Windows 10 IoT Enterprise 2016 LTSB	Pre-load Windows 10 (64-bit) OS

ITEM	HEIGHT	WIDTH	DEPTH
Pro-X Hybrid Kiosk with Short Pin Pad Arm			
Toshiba T10	612.09 mm (24.10 in)	409.83 mm (16.14 in)	329.88 mm (13 in)
Pro-X Hybrid Kiosk with TAL and Short Pin Pad Arm			
Toshiba T10	688.27 mm (27.10 in)	409.83 mm (16.14 in)	329.88 mm (13 in)
Pro-X Hybrid Kiosk with Long Pin Pad Arm			
Toshiba T10	612.09 mm (24.10 in)	582.12 mm (22.92 in)	329.88 mm (13 in)
Pro-X Hybrid Kiosk with TAL and Long Pin Pad Arm			
Toshiba T10	688.27 mm (27.10 in)	582.12 mm (22.92 in)	329.88 mm (13 in)
Pro-X Hybrid Kiosk with Rotating Base and Short Pin Pad Arm			
Toshiba T10	612.09 mm (24.10 in)	409.83 mm (16.14 in)	329.88 mm (13 in)
Pro-X Hybrid Kiosk with TAL, Rotating Base and Short Pin Pad Arm			
Toshiba T10	688.27 mm (27.10 in)	409.83 mm (16.14 in)	329.88 mm (13 in)
Pro-X Hybrid Kiosk with Rotating Base and Long Pin Pad Arm			
Toshiba T10	612.09 mm (24.10 in)	582.12 mm (22.92 in)	329.88 mm (13 in)
Pro-X Hybrid Kiosk with TAL, Rotating Base and Long Pin Pad Arm			
Toshiba T10	688.27 mm (27.10 in)	582.12 mm (22.92 in)	329.88 mm (13 in)

TCB15058-USEN-01  
Released March, 2021