

SCAN MODULES

• Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
• ZEBEX is the trademark of ZEBEX INDUSTRIES INC., all rights reserved.

Z-5160

Middle-Range CCD Scan Module

The middle-range scan module that offers an easy-to-integrate design with an advanced scanning performance. Integrate Z-5160 into your equipment has never been easier or more hassle-free.

- Advanced scanning performance
- Smart and compact design
- Flexible communications

OPERATIONAL	
Light Source	617 nm visible LED
Optical System	Linear CCD array
Microprocessor	32 bit
Depth of Field	280 mm (EAN-13 100%, PCS=90%)
Scan Rate	330 scans per second
Minimum Bar Width	0.1 mm (0.07 mm actually); (Code 39, PCS=90%)
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Two-color LED (green & red)
Beeper Operation	Programmable tone & beep time
System Interfaces	Keyboard wedge, RS-232C, HID USB, USB – Virtual COM Port Emulation
PHYSICAL	
Dimensions	80.0 × 65.0 × 30.3 mm
Weight	150 g
Cable	Standard 2M straight
POWER	
Input Voltage	5 VDC ±10%
Operating Current	120 mA
REGULATORY	
EMC	CE & FCC DOC compliance
ENVIRONMENTAL	
Operating Temperature	0°C – 50°C (32°F – 122°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	20% – 95% RH (non-condensing)
Light Levels	0 – 100,000 Lux



 Free JavaPOS & OPOS Software
Utilities Download Available

