

Z-5652 Plus



2D Image Scan Module (Preliminary)



Lighting speed without compromising performance, the scanner features a powerful 2D engine that easily decodes most 1D and 2D barcodes with intuitive aiming accuracy. It also excels at reading barcodes on smart phone screens and barcodes that are poorly printed. It is the perfect solution for medical industry, retail stores, smart phone applications, and the banking industry.

- Exceptional motion tolerance.
- High speed and reliable performance on all common 1D and 2D codes.
- Captures barcodes on mobile phone, tablet, or computer screens.
- Highly flexible design for easy mounting.



1. Compact size for easy installing.
2. LED indication, buzzer, trigger button.
3. Tripod socket & mounting holes.



- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.

OPERATIONAL

Aiming Element	617 nm LED
Illumination Element	617 nm LED
Optical System	752H × 480V pixels (WVGA)
Scan Angle	44.4° H x 29.1° V
Sensitivity	360° (omnidirectional rotational sensitivity)
Depth of Field	Code39 (5 mil) : 65 - 115 mm EAN 13 (13 mil) : 40 - 250 mm <i>(Note : DOF may vary depending on environment condition and barcode quality.)</i>
Minimum Resolution	5 mils (Code39)
Print Contrast	30% @ UPC/EAN 100%
Indicator	Two-color LED (blue, red)
Programmable Operation	Scan mode, Beeper tone
System Interface	RS-232, USB

PHYSICAL

Dimension	42.6 × 24.3 × 63.3 mm (device only)
Weight	110 g
Interface Cable	Standard 2M straight

POWER

Input Voltage	5 VDC ± 10%
Operating Current	440 mA typical

REGULATORY

EMC	CE & FCC DOC compliant; VCCI; BSMI
Safety	IEC 62471 Exempt

ENVIRONMENTAL

Operating Temperature	0°C – 50°C (32°F – 122°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	5% - 95% RH (non-condensing)
Drop Durability	Designed to withstand 1.5M drops
Light Level	Max. 100,000 Lux

DECODING CAPABILITY

1D Barcode	UPC/EAN (UPCA/UPCE/ EAN-8/ EAN-13, ISBN (Bookland), ISSN), Code 39 (Standard, Full ASCII, Trioptic, Code 32 (Italian Pharmacode), Code 128, Code 93, Codabar, 2 of 5 (Interleaved 2 of 5, Discrete 2 of 5, IATA, Chinese 2 of 5, Matrix 2 of 5, Code 11), MSI Plessey, GS1 DataBar (Omnidirectional, Truncated, Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked)
2D Barcode	PDF417, MicroPDF417, Composite Codes (CC-A, CC-B, CC-C), Aztec (Standard, Inverse), Maxicode, Data Matrix/ ECC 200 (Standard, Inverse), QR Code (Standard, Inverse, Micro)