

MK238XMS

Touch Display S-Line

We trust in **capacitive touch technologies** (PCAP). Depending on your requirements, the display comes fitted with additional features like touch through glass or mirror displays



Touchscreen



DISPLAY FEATURES

Panel Type:	23.8" Multitouch
Resolution (max.):	1920 x 1080 (FullHD) 16:9
Pixel Pitch:	0.2745 mm
Diagonal/ Picture size:	60,4 cm / (W x H): 527.0 x 296.5 mm
Colour Performance:	16.7 Mio
Viewing Angle:	H, V (CR ≥ 10): 178° / 178°
Contrast (static):	1000:1
Brightness:	250 cd/m2
Response Time:	14 ms
Operating Voltage:	12V DC (24V DC optional) / external power supply
Power Consumption:	<24 W
Operating temp./hum.:	±0 ~ +50 °C ; 20 ~ 90% humidity
Storage temp./hum.:	-20 ~ +60 °C ; 10 ~ 90% humidity
Dimensions and Weight:	559.2 x 334.5 x 48.5 mm (W x H x D); 5.1 kg

INTERFACE

Connectivity:	VGA / DVI / HDMI / DP / Audio out / USB
---------------	---

FEATURES

Operating control:	On/off switch, 4 button OSD, auto button
Functions:	Contrast, Brightness, vertical and horizontal image position, phase, pixel clock, 1 user, 2 pre-installed colour temperatures, colour weighting, OSD, input source
Touch:	PCAP Projected Capacitive Thickness: 2,7mm, Hardness: 6H
Controller:	EETI 10-point Multitouch USB

**IMMER AM SCHIRM,
MONITORE DIE PASSEN.**

Tel. +43 7229 23023
Fax +43 7229 230231
eMail info@mikka.com
Web www.mikka.com

MIKKA GmbH
Traunfuerstrasse 110
4052 Ansfelden
Austria